

# MSP231

## HDMI To USB 3.0 Capture



### Key Features

- Plug and play, driver free on Win 10
- Support 4K@30Hz input
- Microphone audio mix and audio output
- USB 3.0 Power supply and mini USB power backup
- LED indicator

### Specification

<b>Connectors</b>	Input	HDMI	1×HDMI-A
	Output	HDMI	1×HDMI-A
		USB 3.0	1×USB-A
	Audio	Mic	1×3.5mm Jack
		Line Out	1×3.5mm Jack
Power		1×Mini USB	
<b>Performance</b>	Input Resolutions	HDMI	
		SMPTE	720p@50/60   1080i@50/60   1080p@23.98/24/25/29.97/30/50/59.94/60   2160p@24/25/30
		VESA	640×480@60   800×600@60   1024×768@60   1280×1024@60   1920×1080@60   3840×2160@24/25/30   4096×2160@24
	Output Resolutions	HDMI (Loop)   USB (output resolution is not configurable)	
	SMPTE	1080p@60	
	VESA	1920×1080@60	
Supported Standard	HDMI	1.4	
	USB	3.0	
<b>Power</b>	Input Voltage	DC 5V 2A	
<b>Environment</b>	Working Temperature	-0 ~50℃	
	Humidity	20 - 90%	
<b>Physical</b>	Weight	Net (Device) 0.25kg	
	Dimensions	Net (Device) 113.5mm×58.7mm×24mm	

### Application



### Order Codes

Product Code	Item
601-0231-00-0	MSP231

Tel: +86-592-5771197 | Fax: +86-592-5788216 | E-mail: sales@rgbink.com  
 Headquarter: S601 Weiye Building, Torch Hi-Tech Development Zone, Xiamen, Fujian, P.R.C.

Specifications are correct at time of printing and subject to change or alteration without notice.

**RGBlink®**  
 www.rgbink.com

