

## Specification

Connectors	Input	HDMI 1.3	2×HDMI-A	
		USB 3.0	2×USB TypeA	
	Output	HDMI 2.0	1×HDMI-A	
	Record	USB 2.0	1×USB TypeA	
	Audio	In	1×3.5mm Audio Jack	
	Out	1×3.5mm Audio Jack		
Communication/Stream	LAN	1×RJ45		
	Power	1×USB-C		
Performance	Input Resolutions	HDMI		
		SMPTE	720p@50/60   1080p@23/24/60	
		VESA	1024×768@60   1280×720@60   1280×800@60   1280×1024@60   1360×768@60   1600×1200@60   1680×1050@60   1920×1080@60	
	Output Resolutions	HDMI		
		SMPTE	720p@50/60   1080p@24/25/50/60   2160p@60	
		VESA	1024×768@60   1280×720@50/60   1280×800@60   1280×1024@60   1360×768@60   1920×1080@50/60   3840×2160@60	
Supported Standard	HDMI	1.3(in)   2.0(out)		
	USB	3.0		
Screen Feature	Screen Dimension	5.5" TFT		
	Resolution	1080×1920 pixels		
	Dot Pitch	0.063(H)×0.021(W)(mm)		
	Aspect Ratio	16:9		
	Brightness	450cd/m <sup>2</sup>		
	Contrast	1000:1		
Power	Backlight	LED		
	View Angle	80°/80°(L/R)80°/80°(U/D)		
	Input Voltage	9V/2A		
	Max Power	18W		
	Environment	Temperature	0°C ~ 55°C	
	Humidity	5%~85%		
Physical	Weight	Net	350g(without battery);882g(with battery)	
		Package	770g	
	Dimension	Net	161mm×106mm×36mm	
		Package	255mm×145mm×85mm	
Order Codes	Product Code	410-5513-01-0	TAO 1 pro	
		490-5513-01-1	TAO 1 pro-S	
		490-5513-01-0	TAO 1 pro lithium battery(optional)	






**TAO 1 pro**

Talent Anchor Online



## Dimension



**RGBlink**

Proudly designed and manufactured in Xiamen Hi Technology Zone, China  
 WEB: www.rgblink.com EMAIL: sales@rgblink.com PHONE: +86 592 5771197



www.rgblink.com

**RGBlink**

TAO 1pro is a Broadcasting streaming decoder with a 5.5 inch FHD preview display, but also a 4 channels seamless video switcher for 2 USB 3.0 and 2 HDMI 1.3 inputs, and supports streaming directly by ethernet output which is ready to connect to external cloud based router and streaming from Anywhere to Everywhere.

TAO 1pro is compatible with standard USB 2.0 and USB 3.0 cameras by UVC protocol, and brings itself as a much affordable and user friendly streaming tools for anybody, the talents who is willing to be Anchor Online.

TAO 1pro is also with touch panel for finger configuration, and with optional 2 chargeable battery extending its capacity for outdoor application.

Scene 1: Seamless switching between USB and HDMI inputs




Scene 2: Seamless switching between different USB inputs



# TAO 1pro

Talent Anchor Online



## Key Features



· 5.5-inch touchscreen operation



· Multistream up to 4 Live Streaming platform Simultaneously



· Fast image processing



· USB and HDMI signal multicasting



· video monitoring



· Bluetooth 5.0



· Dual battery Options



· Extending Monitor



· Recording via USB 2.0 port



· NDI5.0 Encoder

Scene 3: Ready for Bluetooth remote control



Scene 4: Input preview and extending monitor (90° supported)



Scene 5: Outdoor wireless streaming

